

Student:

<https://quizapp.itiskill.com/student/join?quiz=ITISKILL5502JT>

Score: 6/25 (24.00%)

Code: 2689

1. Which is elastic material?

- A) **Nylon** B) Polystyrenes
C) Celluloid D) Polycarbonates (Incorrect)

2. Which is thermo plastic material?

- A) Butyl rubber B) Nylon
C) Neoprene (Incorrect) D) **Vinyl polymers**

3. What is the maximum percentage of stretch of its original length is allowable for elastic materials?

- A) 100% B) 200%
C) **300% (Correct)** D) 400%

4. What is the ratio between the change in dimension to its original dimension of the substance?

- A) Stress (Incorrect) B) **Strain**
C) Poisson's ratio D) Factor of safety

5. What is the unit of strain?

- A) Kg/cm² (Incorrect) B) Newton/metre²
C) Metre D) **No unit**

6. What is the ratio of change in length to original length?

- A) **Linear strain** B) Lateral strain
C) Volumetric strain D) Poisson's ratio (Incorrect)

7. What is the ratio between lateral strain and longitudinal strain?

- A) Hooks law (Incorrect) B) Young's modulus
C) Bulk modulus D) **Poisson's ratio**

8. Which symbol is used to express change in length?

- A) L B) **delta l (Correct)**
C) I D) e

9. Which one is the ratio of stress?

- A) **Load and area** B) Load and direction (Incorrect)
C) Load and diameter D) Load and time

10. Which force acts on rivets?

- A) Tensile force (Incorrect) B) Compressive force
C) **Shear force** D) Bending force

11. What is the formula for bulk modulus?

- A) Tensile stress/Tensile strain (Incorrect) B) Compressive stress/Compressive strain
C) **Volumetric stress/Volumetric strain** D) Shear stress/Shear strain

12. Which law states that within elastic limit stress is directly proportional to strain?

- A) Newtons law B) **Hooks law (Correct)**
C) Joules law D) Charles law

13. What is the term used for maximum stress attained by a material before rupture?

- A) Tensile stress B) Compressive stress
C) Working stress D) **Ultimate stress (Correct)**

14. What is the ratio between ultimate stress to working stress?

- A) Bulk modulus (Incorrect) B) Young's modulus
C) **Factor of safety** D) Modulus of rigidity

15. What is the ratio of ultimate load to area of original cross section?

- A) Factor of safety B) Yield point
C) **Ultimate stress** D) Youngs modulus (Incorrect)

16. What is the ratio of shear stress to shear strain?

- A) Modulus of elasticity (Incorrect) B) **Modulus of rigidity**
C) Bulk modulus D) Yield point

17. What is the ratio between stress and strain?

- A) Yield point (Incorrect) B) Factor of safety
C) **Youngs Modulus** D) Poisson's ratio

18. Which force acts on crank shaft?

- A) Shear stress B) **Torsional stress (Correct)**
C) Tensile stress D) Compressive stress

19. Which is thermosetting plastic?

- A) Vinyl polymers B) Polystyrenes
C) Celluloid (Incorrect) **D) Melamine resins**

20. What force will be required to punch a hole of 10 mm dia in a 1 mm thick plate, if the allowable shear stress is 50 N/mm^2 ? ($\pi = 22/7$)

- A) 1757 N B) 1575 N (Incorrect)
C) 1571.4 N D) 1577 N

21. What is the tensile stress if a square rod of 10 mm side is tested for a tensile load of 1000 kg?

- A) 1 kg/mm^2 (Incorrect) **B) 10 kg/mm²**
C) 100 D) 1000
 kg/mm^2 kg/mm^2

22. What is the tensile strain if a force of 3.2 kN is applied to a bar of original length 2800 mm extends the bar by 0.5 mm?

- A) 0.0001786** B) 0.0001687

- C) 0.0001867 (Incorrect) D) 0.0001968

23. How much strain is developed in an iron rod of 1 metre length gets elongated by 1 cm, if a force of 100 kg is applied at one end?

- A) 0.1 (Incorrect) **B) 0.01**
C) 0.001 D) 0.0001

24. What is the young's modulus if a wire of 2m long, 0.8 mm² in cross section increases its length by 1.6 mm on suspension of 8 kg weight from it?

- A) 1.25 kg/mm^2 (Incorrect) B) 12.5 kg/mm²
C) 125 **D) 12500**
 kg/mm^2 **kg/mm²**

25. What is the safe stress if the ultimate stress of a material is 35 kg/mm^2 and factor of safety is 5?

- A) 0.143 B) 0.7
C) 1.43 **D) 7 (Correct)**